

■ **Safe Seal (290ml)**



290ml ... Art. nr 01.2427
 20kg ... Art. nr 01.2412
 400ml ... Art. nr 01.2428

Sealants / Glues

Cartridge - 290ml

Safe Seal is a very high-grade, strongly adhesive MS Polymer-based windscreen sealant. This sealant has been specially developed for the fast and professional gluing of car windscreens. Due to its unique composition Safe Seal offers perfect adhesion to old windscreen sealant, glass and ceramic edges, without using a primer.

These properties ensure that no other extra products are necessary when fitting car windscreens with Safe Seal. The chances of making a mistake when fitting are also highly reduced. Therefore, the product simplifies the formerly complex process of fitting these windscreens.

Safe Seal is also free of solvents and isocyanates and does not contain silicones.

Due to its unique composition the product is perfectly UV resistant and so it is extremely well suited to applications in which the sealant edge is exposed to sunlight.

A very good advantage of the product is that it has an extremely high initial strength and this has a positive effect in that the windscreen does not subside, certainly if it has to be placed vertically. In addition, Safe Seal has the very positive property of having high constancy, meaning that the strip of sealant does not collapse during processing. When hard, Safe Seal contributes to the rigidity of the bodywork. Therefore, the product also gives the vehicle very good torsion rigidity.

Due to its use of MS Polymers Safe Seal has a long pot life after opening, and so cartridges need no longer be discarded after opening. The product is also very easy to remove the hands after use. If the fitter gets Safe Seal on his hands after fitting the windscreen this can be washed off easily, and there is no need to carry out the job with dirty hands.

The handy 290 ml cartridges make Safe Seal very economical and easy to use.

Windscreens glued with Safe Seal can be cleaned and de-greased using Innotec Seal and Bond Remover (art.no. 04.0107) or Innotec Multisol (art.no. 04.0151).

Properties:

- Excellent adhesion to old windscreen sealant, glass and ceramic edges without a primer.
- Simple method/ no extra products needed.
- Solvent, isocyanate and silicon free.
- Long storage life, even after opening.
- Easy to remove from hands.
- Good UV resistance.
- Very good constancy / strip of sealant does not collapse.
- Very high initial strength, the windscreen does not subside.
- Good torsion rigidity / contributes to the rigidity of the bodywork.



Only quality has a future

■ **Safe Seal (290ml)**

