

■ **Hi-Temp Wax (Spray - 500ml)**

1/1



1000ml ... Art. nr 02.2428
 Spray - 500ml ... Art. nr 02.2113

Aerosol - 500ml

Hi-Temp Wax is a very durable, transparent anti-rust coating for protecting sheet metal work and cavities. The product has excellent water repellent and penetrating power, as a result of which it penetrates into the smallest cavities and cracks. This provides long-term effective protection for the surface.

Due to its special chemical composition Hi-Temp Wax has an extremely high temperature resistance. The product remains absolutely stable to a temperature of 150°C. Due to its very high temperature resistance Hi-Temp Wax is extremely well suited for use in the engine compartment of the vehicle and in engine rooms - the product will not run off.

Hi-Temp Wax can be used to protect metal and sheet metal against corrosion during construction or repairs. The product is mostly applied to the inside of doors, chassis parts, beams, etc.

Hi-Temp Wax can also be applied with effect to protect power points, battery poles and other electrical components subject to the effects of weather, dampness, dirt and salt. Hi-Temp Wax ensures that these parts are highly water-repellent, as a result of which faults due to permeating dampness or corrosion can be kept to a minimum.

Hi-Temp Wax is available in two types of packaging; in an aerosol can and in a 1 litre can.

The 1 litre can is very economical and perfectly sprayable with the InnoQuip Pressure Pot Gun (art.no. 90.0946). The wide range of settings available on this pistol allow you to spray layers of any thickness. For optimal treatment of cavities use the Cavity Tube Set (art.no. 90.1001).

Thanks to its aerosol packaging it is extremely user friendly and easy to apply. When first applied the product is liquid, allowing it to penetrate deep between the parts. When the propellant disappears it leaves a beautifully lasting and pressure-resistant grease behind. The extra nozzle and tube supplied with the product make it very easy to apply in places which are difficult to access. For optimal treatment of cavities use the Hi-Temp Wax Spray Tube (art.no. 90.2982). Properties:- Good liquidity properties during application.

- No long-term leaking after application.
- Perfect protection against rust.
- High temperature resistance (up to +150°C). The product does not return to liquid state even in extremely hot conditions.
- Impervious to many chemicals such as brake fluid, salt, etc.